

SECTION A-A


NOTES:

1. INSTALL ϕ 3/32 HEATSHRINK (157-0003) OVER SOLDER SPLICE.
2. CUT UNUSED WIRES FLUSH WITH SPLICE AND COVER WITH ϕ 3/32 HEATSHRINK (157-0003).
3. LUBRICATE O-RING WITH DOW CORNING #55 OR EQUIVALENT.
4. SECURE CONNECTOR STUD WITH LOCTITE 242 OR EQUIVALENT.
MAX TIGHTENING TORQUE 125 lbs-in.
5. CRIMP CONTACTS WITH BERG TOOL (HT-95).
6. APPLY RED NAIL POLISH ACROSS CONNECTOR BODY/ENDCAP TO SIGNIFY PART HAS BEEN TIGHTENED.
7. DIMENSIONS IN INCHES.
8. DO NOT SCALE.

PROPRIETARY NOTICE
 THIS DOCUMENT CONTAINS INFORMATION WHICH IS SOLE PROPERTY OF KONGSBERG MESOTECH LTD AND IS RECEIVED IN CONFIDENCE. ITS CONTENTS MAY NOT BE DISCLOSED OR REPRODUCED IN ANY WAY WITHOUT WRITTEN CONSENT OF KONGSBERG MESOTECH LTD.

APPROVALS	NAME	DATE
DRAWN	DL	08/04/08
REVISED	DL	11/09/08
CHECKED		
ENGR		
ISSUED		

DO NOT SCALE DRAWING.
 CONFIDENTIAL. DO NOT COPY.



1.2	ECO 4838	11/09/08
1.1	ECO 4654	10/06/08
ISS	DESCRIPTION	DATE

REVISIONS

Kongsberg Mesotech Ltd.
ASSEMBLY DRAWING -
4000m ENDCAP
BURTON 55 SERIES, SHELL 15 CONN.

SIZE	NSCM NO	TYPE	DWG. NO.	ISS
B	1C965	MD	442-02011000	1.2
SCALE: 1:1		W.O. NO.		SHEET 1 OF 1